

OBSCURA XP

MULTI-MISSION CAMERA



Wide-Angle Lens

Real-Time Situational Awareness & Actionable Intelligence

Body-worn POV | Surveillance Operations | Modular Mounting Options

Obscura XP Multi-Mission Camera is a ruggedized (IP66), miniature HD IP Camera capable of streaming and/or optionally recording high-resolution 3.1MP video and audio in day-light or low-light environments. With an 85° field of view for the base model, 135°/140° for the wide-angle version, built-in infrared illuminator, microphone & SD card, and modular mounting options, Obscura XP provides flexibility for use in body-worn, concealment or remote surveillance operations.

Natively compatible with all StreamCaster 4000-series MANET radios, the Obscura XP features an intuitive web-interface, allowing users to access video downlink and customize image quality, camera settings and video capture parameters.

SILVUS
TECHNOLOGIES

LEADING THE MIMO REVOLUTION

OBSCURA XP


MULTI-MISSION CAMERA



Universal Mounting System
1/4-20 Mounting Plate & Clip
Included

KEY FEATURES

- HD Resolution Video – H.264, H.265, H.256+
- 85° Field of View; 135°/140° for Wide-Angle; Motion Detection
- Built-In Infrared Illuminator – Excels in low-light conditions
- On-board Microphone & SD Card (30GB; Recording Version)
- Multiple Interface Options – Ethernet, USB 2.0 (Nett Warrior)



GENERAL

MAX RESOLUTION	2048 X 1536 (3.1MP)
FIELD OF VIEW	85°; 135°/140° for Wide-Angle
FRAME RATE	Adjustable 1-30fps
BIT RATE OPTIONS	CBR/VBR (64 to 5120kbps)
VIDEO ENCODING	H.264, H.265, H.256+
AUDIO ENCODING	G.711, G.711a and AAC Adjustable Audio Settings
INTERFACE CONNECTOR – ETHERNET VERSION	10/100 Ethernet (6-Pin Switchcraft (f))
INTERFACE CONNECTOR – USB 2.0 VERSION	USB 2.0 (6-Pin Nett Warrior (m))
STREAMING PROTOCOLS	RTSP, RTP, UDP, TCP, IGMP Multicast
POWER	5VDC 1.7 nominal, 2.5W with IR LED
ONBOARD RECORDING (OPTIONAL)	30GB SD Card (non-removeable, recording version only)
INFRARED LED ILLUMINATOR	Integrated Light Sensor To Detect Light Intensity IR LED On < 3 (±2) LUX, IR LED Off > 8 (±2) LUX
WEIGHT	3 oz. (85g)
CAMERA DIMENSIONS	1.86" x 1.86" x 0.80" (47.4 x 47.4 x 22.6 mm)
OPERATING CONDITIONS	-10°C to +50°C (-14°F to +122°F); IP66
ADDITIONAL FEATURES	ONVIF Compliant Intuitive Web-Interface Compatible with a variety of VMS including Airship and Milestone Physical IR LED/CUT Switches

DISTRIBUTOR



+1 503.434.6845
+1 503.217.6080
customerservice@nwuav.com
www.nwuav.com

11160 SW Durham Lane | McMinnville, OR 97128 USA

www.silvustechologies.com

The following notice applies to the sale, lease, or offer of this device other than for use by the United States Government or for export: This device has not been authorized as required by the rules of the Federal Communications Commission. This device is not, and may not be, offered for sale or lease, or sold or leased, until authorization is obtained. Please contact Silvus for questions about the FCC approval status or requirements that pertain to this device including whether an FCC approved version is available. Exported devices are subject to the laws of the countries into which they are exported.